




FAG

UC207-22

Radial insert ball bearing

Radial insert ball bearings UC, spherical outer ring, location by grub screws, RSR seals on both sides

Informacje techniczne



Main Dimensions & Performance Data

d	34,925 mm	Bore diameter
d	34,925 mm	Bore diameter, inch
D _{SP}	72 mm	Outside diameter
B	42,9 mm	Width
C _{0r}	15.300 N	Basic static load rating, radial
C _{ur}	800 N	Fatigue load limit, radial
C _r	27.500 N	Basic dynamic load rating, radial
≈m	0,447 kg	Masa

Dimensions

C	20 mm	Width, outer ring
C ₂	20,6 mm	Sealing total width
S	17,5 mm	Distance raceway
d ₁	46,84 mm	Rib diameter inner ring
C _a	5,7 mm	Distance to lubrication hole
A	7 mm	Distance thread

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Calculation factors

f ₀	13,8	Calculation factor
----------------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna