

FAG

UCFA207-22

Take-up housing unit

Housing units UCFA, cast iron housing, radial insert ball bearing with grub screws in inner ring, RSR seals, for swivel motion

Informacje techniczne





Twoja aktualna wersja produktu

Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	34,93 mm	Bore diameter
L	161 mm	Length total
U	44,4 mm	Total height unit
≈m	1,257 kg	Masa

Mounting dimensions

N	14 mm	Fixing bore
N_1	66 mm	Length (slot)
N_2	14 mm	Width (slot)
J	130 mm	Distance fixing bore

Dimensions

A_1	16 mm	Thickness of flange
A_2	19 mm	Distance raceway
A	34 mm	Height housing
V	90 mm	Shoulder diameter housing
W	82 mm	Width housing slot side
Q	M6	Connection thread for lubrication

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Additional information

	FA207	Housing
	UC207-22	Bearing designation

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje