

FAG

UCFA211-32

Take-up housing unit

Housing units UCFA, cast iron housing, radial insert ball bearing with grub screws in inner ring, RSR seals, for swivel motion

Informacje techniczne





Twoja aktualna wersja produktu

Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	50,8 mm	Bore diameter
L	219 mm	Length total
U	58,4 mm	Total height unit
≈m	3,11 kg	Masa

Mounting dimensions

N	16 mm	Fixing bore
N_1	86 mm	Length (slot)
N_2	16 mm	Width (slot)
J	184 mm	Distance fixing bore

Dimensions

A_1	20 mm	Thickness of flange
A_2	25 mm	Distance raceway
A	43 mm	Height housing
V	130 mm	Shoulder diameter housing
W	104 mm	Width housing slot side
Q	M6	Connection thread for lubrication

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Additional information

	FA211	Housing
	UC211-32	Bearing designation

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje