


**ZKLN2557-2RS-XL**

Axial angular contact ball bearing

Axial angular contact ball bearing  
ZKLN...-2RS-XL, double direction, no screw  
mounting

X-life

## Informacje techniczne



## Twoja aktualna wersja produktu

|                 |          |                                 |
|-----------------|----------|---------------------------------|
| Sealing         | 2RS      | Contact lip seals on both sides |
| Tolerance class | Standard |                                 |

## Main Dimensions &amp; Performance Data

|                          |             |                                       |
|--------------------------|-------------|---------------------------------------|
| d                        | 25 mm       | Bore diameter                         |
|                          | 0 mm        | Bore diameter upper tolerance         |
|                          | -0,005 mm   | Bore diameter lower tolerance         |
| D                        | 57 mm       | Outside diameter                      |
|                          | 0 mm        | Outside diameter upper tolerance      |
|                          | -0,01 mm    | Outside diameter lower tolerance      |
| B                        | 28 mm       | Width                                 |
|                          | 0 mm        | Width upper tolerance                 |
|                          | -0,25 mm    | Width lower tolerance                 |
| C <sub>a</sub>           | 30.500 N    | Basic dynamic load rating, axial      |
| C <sub>0a</sub>          | 55.000 N    | Basic static load rating, axial       |
| C <sub>ua</sub>          | 3.350 N     | Fatigue load limit, axial             |
| n <sub>G</sub><br>Grease | 5.700 1/min | Limiting speed for grease lubrication |
| n <sub>g</sub>           | 2.600 1/min | Thermally safe operating speed        |
| M <sub>R</sub>           | 0,4 Nm      | Bearing frictional torque             |
| ≈m                       | 0,354 kg    | Masa                                  |



Mounting dimensions

|                    |       |                             |
|--------------------|-------|-----------------------------|
| D <sub>a</sub> max | 48 mm | Maximum diameter of housing |
| d <sub>a</sub> min | 32 mm | Minimum diameter shaft      |

Dimensions

|                    |         |                           |
|--------------------|---------|---------------------------|
| d <sub>1</sub>     | 40,5 mm | Rib diameter inner ring   |
| r <sub>min</sub>   | 0,3 mm  | Minimum chamfer dimension |
| r <sub>1 min</sub> | 0,6 mm  | Minimum chamfer dimension |
| α                  | 60 °    | Contact angle             |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |

Additional information

|                 |              |                                                             |
|-----------------|--------------|-------------------------------------------------------------|
| c <sub>aL</sub> | 750 N/μm     | Rigidity axial                                              |
| c <sub>kL</sub> | 200 Nm/mrad  | Tilting rigidity                                            |
| M <sub>m</sub>  | 0,486 kg*cm2 | Mass moment of inertia                                      |
|                 | 2 μm         | Axial runout                                                |
|                 | ZM25         | Recommended INA precision locknut for radial locking        |
|                 | AM25         | Recommended INA precision locknut for axial locking         |
| M <sub>A</sub>  | 25 Nm        | Tightening torque for the recommended INA precision locknut |
|                 | 9.123 N      | Required locknut force axial                                |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne